



Simple Solutions



Distribuido por:

Instrumentos de Medición Especializados, S. de R.L. de C.V.

Empresa del Grupo **IDIMEX**

Dr. Velasco No.95 Edificio 9 – 204 Col. Doctores. Delegación Cuauhtémoc. México, D. F. C. P. 06720

Tel. Internacional + (52) Nacional 01 (55) 5588 94 79, 5588 94 66, 5588 53 45, 5588 55 28, 5588 95 49.

Fax : Ext. 206

E-mail: idimex@prodigy.net.mx

www.grupoidimex.com.mx



Boletín IME090226G



N/P: CPL72N300V Dimensions: 72x72
N/P: CPL72N500V Dimensions: 72x72
N/P: CPL96N300V Dimensions: 96x96
N/P: CPL96N500V Dimensions: 96x96

AC Voltmeter



N/P: CPF72N55-65HZ Dimensions: 72 x 72
N/P: CPF96N55-65HZ Dimensions: 96 x 96
Voltage: 220VAC

Frecuencymeter



N/P: CPT72N X /5A Dimensions: 72 x 72
N/P: CPT96N X /5A Dimensions: 96 x 96

AC Ammeter 5/A



N/P: CP-H48 Dimensions: 48 x 48
N/P: CP-H72 Dimensions: 72 x 72
N/P: CP-H96 Dimensions: 96 x 96
Voltage: 220 - 250 VAC
60HZ

Hour run meter



Ammeter Selector

N/P: CP-AS-IG
Function: 3 phase 4 wire
Stage: 3
Rating: 20 A



Voltage Selector

N/P: CP-VS-IG
Function: 3 phase 3 wire
Stage: 2
Rating: 20 A



CTS

N/P: TC/5 100 N/P: TC/5 800
N/P: TC/5 150 N/P: TC/5 1000
N/P: TC/5 200 N/P: TC/5 1200
N/P: TC/5 250 N/P: TC/5 1500
N/P: TC/5 400 N/P: TC/5 1800
N/P: TC/5 500 N/P: TC/5 2000
N/P: TC/5 600 N/P: TC/5 2500



Emergency stop button

N/P: CP-ES-G
Head: 40mm
Contact Block: N.O. & N.C.
Ui=300V
Ith=5A
Twist-Release Operation



N/P: 701-00 702-10 HR



N/P: 501 (L-N)



N/P: BEC100 = ASM150



N/P: 3110-01



N/P: 704 www.deepseapl.com



Norms and Quality Certificates

Distribuido por:

Instrumentos de Medición Especializados, S. de R.L. de C.V.

Empresa del Grupo **IDIMEX**

Dr. Velasco No.95 Edificio 9 – 204 Col. Doctores. Delegación Cuauhtémoc. México, D. F. C. P. 06720

Tel. Internacional + (52) Nacional 01 (55) 5588 94 79, 5588 94 66, 5588 53 45, 5588 55 28, 5588 95 49.

Fax : Ext. 206

E-mail: idimex@prodigy.net.mx

www.grupoidimex.com.mx



Boletín IME090226G